20 款特斯拉 3 头枕音响安装说明

2020 Style Tesla Model 3 Stereo Headrest Installation instruction





1.把座椅靠垫的上图位置用力往下压,露出里面的卡簧 Press down firmly on the seat cushion at the position shown in the figure above,Expose the snap ring inside.



2.用两把螺丝刀左右同时把卡簧往中间撬开,然后用手用 力把头枕往上拔出 Use two screwdrivers to pry the snap ring apart in the middle on both sides at the same time. Then pull the headrest up and out forcefully.



3.在座椅靠垫后方如上图用手用力掰出 Pry out the panel behind the seat cushion forcefully as the figure shown above.



4.座椅靠垫后方盖板主要是上图红圈内两个卡扣固定的 There are two buckle fixed in the seat cushion panel.See the red circle.



5.拆掉副驾脚窝膝盖处饰板找到行程电脑,电源和协议转 接灰色插头 Remove the panel in front the passenger seat to find the trip computer



6.音频信号转接上图白色插头 Audio signal cable connect the white plug as the figure shown above.



7.主驾 A 柱下方找到蓝色插头拔出转接 Find the blue socket under the A pillar in the driver's cab



8.ECU 控制盒如上图对插 Plug the ECU Control box as the figure shown above.



9.把 ECU 控制盒隐藏在马鞍有空隙的位置即可 Hind the ECU control box under the seat.



10.头枕线在 ECU 控制盒处穿到马鞍主驾一侧,然后从膝 盖饰板内走到门沿橡胶一直到座椅后方(如上图红线示 意) Pass through the headrest cable to the another side of the driver's cab, and thread it to the back of the seat.(as the figure shown above.)



11.走线到座椅后方与上图红框内原车线用扎带绑在一起 Thread the cable to the back of the seat, and bind with the original wire here.



12.插头与安装好后的音响头枕对插,测试完好即可复原 Plug to the installed stereo headrest, recover it after test.